

SETS - ARMORED PERSONNEL CARRIER




SETS - Armored Personnel Carrier

Each unit is built to stringent quality levels and can be adapted to any of our client's individual specifications. Various levels of protection can be offered as well as a full range of accessories offered to the armored vehicle industry. The excellent design, workmanship and reliable performance continues to impress our clients everywhere in the field of application. The modular interior layout of the SETS APC can, at additional costs, be changed to re-configure the vehicle for any one of the following roles:

- . Command and control vehicle
- Tactical patrol vehicle
- Tactical fire-support vehicle
- Tactical ambulance with stretcher for patients

We offer our users a package of total life cyclcycle support providing maintenance, repair and engineering services, logistics information, product support, training and field support.





Technical Datas

Length: 5883mm Width: 2363mm

Height: 2468mm

Wheel Base: 3412mm

Ground Clearance: 343mm (under axle)

Angle of Approach: 43°

Tare: 7100kg

Payload: 2870kg **GVM:** 9970kg

Seating: driver + 10 Top Speed: 110km/h+

Gradeability: 70% low range **Turning Circle:** 15m (curb to curb)

Standard Tank Size: 150 litres

Tank Range: 600 km

Tank Optional: 300 litres / range 1200 km

Ballistic Protection: B6 upgradeable to B7

Mine Protection: 2 x Tm57 landmines or equivalent under any wheel

x Tm57 landmine or equivalent directly under hull

Engine Make: mWm

Engine Model: 4.10T (upgradable to 6.1)

Engine Type: diesel-Turbo charged, 4 cylinder in line, water cooled

upgradeable to 6 cylinder

Displacement: 4300cm3

Max Power: 103 kw @ 2600 rpm (*upgradeable to* 154 kW/206 hp)

Max Torque: 412 Nm @ 1600 rpm (upgradeable to 670 Nm)

Transmission Make: Allison

Transmission Type: Automatic with lock up

Transfer Case Make: rockwell 232

2 Speed

Transfer Case Type: Steering System:

hydraulically assisted re-circulated ball

RHD/LHD: left or right hand drive

Axles Make: rockwell

Suspension: Semi elliptic leaf springs with double acting telescopic,

nydraulic shock absorbers

Service Brakes: Full pneumatic dual circuit

Emergency Brakes: Pneumatic spring brake


Solid pressed 20" Shallow disc Rim Type:

Tyres: 12,5 x 20

Transportability: 2 Units per c130 / 1 Unit per 6m container









The SETS APC has been tested on special test tracks under worst case conditions to ensure performance in the harshest of terrain.







SETS-Group AG Security Equipment Technologie Swiss